


Product data sheet

KAP 145
03.4420.B1/PH LED/17,8W
FLOS



Luminaire with embedded installations on ceilings for halogen lamps and metal halide. The Easy Kap version, incorporates body injected in zamak with liquid paint finish and outer diameter of 105mm with opal glass diffuser. Pre-frame instalation not necessary. The Kap version incorporates body injected in aluminium with liquid paint finish. It is available in two sizes: 105mm and 145mm, always in No Trim installation. Main view made of anodized gloss aluminium with diffuser element made in borosilicate glass. Lampholders with heatsink element in injected aluminium and embedment ring of the optical body in thermoplastic material. Finishings: white (B1), matt gold (GL), blue (BU) and black (74).

Light output 1



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 17.8 W | LOR | 55% |
| Lamp flux | 1300 lm | Total flux | 720 lm |
| Luminous efficacy | 73 lm/W | Total power | 17.8 W |
| CCT | 3000 K | | |
| CRI | 80 | | |

Mounting mode

Ceiling recessed

Shape and measurements

Height: 6.50 in
Diameter: 5.71 in

Adjustability

Fixed

Electric

System power: 17.8 W
Appliance Class: II

Protection

IP: 43