
Product data sheet

PML WITH BRACKET LIVORNO S DOUBLE 4000K 10.14102.0VXXX + 10.34101.2V001

HESS



Design luminaire body made of cast aluminium. Luminaire enclosure made of single-pane safety glass, opens without tools. LIVORNO S: Luminaire for pole top mounting. Fitted with LED up to approx. 53W. LIVORNO XL: Luminaire for pole top and side mounting. For pole top mounted installation, angle of 0° and 5° possible. Fitted with LED up to approx. 107W. 10.34101.2V001 ZOPF 76,1 MM Bracket LIVORNO 400 double Made of galvanised steel Projection 800 mm Spigot ø 76,1 mm (pole + luminaire) Colour: DB 703

Light output 1



1 x LED			
Nominal lamp power	37 W	LOR	100%
Lamp flux	5141 lm	Total flux	5141 lm
Luminous efficacy	139 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	2588 lm	Total flux	2588 lm
Luminous efficacy	129 lm/W	Total power	20 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	20 W	LOR	100%
Lamp flux	3174 lm	Total flux	3174 lm
Luminous efficacy	159 lm/W	Total power	20 W
CCT	4000 K		
CRI	80		



Nominal lamp power	20 W	LOR	100%
Lamp flux	2681 lm	Total flux	2681 lm
Luminous efficacy	134 lm/W	Total power	20 W
CCT	4000 K		
CRI	80		




1 x LED

I X LLD			
Nominal lamp power	20 W	LOR	100%
Lamp flux	2483 lm	Total flux	2483 lm
Luminous efficacy	124 lm/W	Total power	20 W
CCT	4000 K		
CRI	80		



1 x LED

===			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3681 lm	Total flux	3681 lm
Luminous efficacy	131 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	28 W	LOR	100%
Lamp flux	3441 lm	Total flux	3441 lm
Luminous efficacy	123 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		



Nominal lamp power	28 W	LOR	100%
Lamp flux	3174 lm	Total flux	3174 lm
Luminous efficacy	113 lm/W	Total power	28 W
CCT	4000 K		
CBI	80		



Nominal lamp power	20 W	LOR	100%
Lamp flux	2767 lm	Total flux	2767 lm
Luminous efficacy	138 lm/W	Total power	20 W
CCT	4000 K		
CRI	80		



1 x LED

I X LLD			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3303 lm	Total flux	3303 lm
Luminous efficacy	118 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	6604 lm	Total flux	6604 lm
Luminous efficacy	125 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		



1 x LED

I X LLD			
Nominal lamp power	37 W	LOR	100%
Lamp flux	5175 lm	Total flux	5175 lm
Luminous efficacy	140 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		



IXLLD			
Nominal lamp power	37 W	LOR	100%
Lamp flux	4773 lm	Total flux	4773 lm
Luminous efficacy	129 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		



Nominal lamp power	37 W	LOR	100%
Lamp flux	5362 lm	Total flux	5362 lm
Luminous efficacy	145 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		



1 x LED

TALLD			
Nominal lamp power	37 W	LOR	100%
Lamp flux	4966 lm	Total flux	4966 lm
Luminous efficacy	134 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	53 W	LOR	100%
Lamp flux	7361 lm	Total flux	7361 lm
Luminous efficacy	139 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		



1 x LED

I X LED			
Nominal lamp power	53 W	LOR	100%
Lamp flux	6882 lm	Total flux	6882 lm
Luminous efficacy	130 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		



Nominal lamp power	53 W	LOR	100%
Lamp flux	6347 lm	Total flux	6347 lm
Luminous efficacy	120 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		






Nominal lamp power	53 W	LOR	100%
Lamp flux	7130 lm	Total flux	7130 lm
Luminous efficacy	135 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		




Nominal lamp power	28 W	LOR	100%
Lamp flux	3565 lm	Total flux	3565 lm
Luminous efficacy	127 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		

Light output 2




1 x LED

Nominal lamp power	37 W	LOR	100%
Lamp flux	5141 lm	Total flux	5141 lm
Luminous efficacy	139 lm/W	Total power	37 W
CCT	4000 K		
CRI	80		



1 x LED


Nominal lamp power	20 W	LOR	100%
Lamp flux	2588 lm	Total flux	2588 lm
Luminous efficacy	129 lm/W	Total power	20 W
CCT	4000 K		
CBI	80		



IXLLD			
Nominal lamp power	20 W	LOR	100%
Lamp flux	3174 lm	Total flux	3174 lm
Luminous efficacy	159 lm/W	Total power	20 W
CCT	4000 K		
CRI	80		


1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	20 W 2767 lm 138 lm/W 4000 K 80	LOR Total flux Total power	100% 2767 lm 20 W
1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	28 W 3303 lm 118 lm/W 4000 K 80	LOR Total flux Total power	100% 3303 lm 28 W
1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	53 W 6604 lm 125 lm/W 4000 K 80	LOR Total flux Total power	100% 6604 lm 53 W
1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	37 W 5175 lm 140 lm/W 4000 K 80	LOR Total flux Total power	100% 5175 lm 37 W
1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	37 W 4773 lm 129 lm/W 4000 K 80	LOR Total flux Total power	100% 4773 lm 37 W

7-42044	1 x LED			
	Nominal lamp power	37 W	LOR	100%
	Lamp flux	5362 lm	Total flux	5362 lm
	Luminous efficacy	145 lm/W	Total power	37 W
	CCT	4000 K		
	CRI	80		
XX				
ANNIWA LA	1 x LED			
	Nominal lamp power	37 W	LOR	100%
	Lamp flux	4966 lm	Total flux	4966 lm
	Luminous efficacy	134 lm/W	Total power	37 W
XXIIIX	CCT	4000 K	'	
XXIIXX	CRI	80		
XXIII				
TAXIII ATT	1 x LED			
	Nominal lamp power	53 W	LOR	100%
	Lamp flux	7361 lm	Total flux	7361 lm
	Luminous efficacy	139 lm/W	Total power	53 W
\times	CCT	4000 K		
	CRI	80		
XIIX				
	1 150			
	1 x LED Nominal lamp power	53 W	LOR	100%
	Lamp flux	6882 lm	Total flux	6882 lm
	Luminous efficacy	130 lm/W	Total power	53 W
	CCT	4000 K	rotal power	00 **
\times	CRI	80		
X TTY				
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX	1 x LED			
	Nominal lamp power	53 W	LOR	100%
	Lamp flux	6347 lm	Total flux	6347 lm
	Luminous efficacy	120 lm/W	Total power	53 W
XX	CCT	4000 K		
	CRI	80		





Nominal lamp power	53 W	LOR	100%
Lamp flux	7130 lm	Total flux	7130 lm
Luminous efficacy	135 lm/W	Total power	53 W
CCT	4000 K		
CRI	80		



Nominal lamp power	28 W	LOR	100%
Lamp flux	3565 lm	Total flux	3565 lm
Luminous efficacy	127 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 36.79 in Width: 4.00 in Height: 12.12 in

Adjustability

Fixed

Electric

System power: 40-106 W

Protection

IP: 65