

# Product data sheet


PETRA PVIII (BOLLARD)  
9.883.5567.10  
LEIPZIGER LEUCHTEN



IP  
55

Decorative luminaire for lanes, driveways, terraces, gardens and for night illumination and hazardous areas. Light exit on two sides. - Impact-resistant opal polycarbonate attachment, UV-stablized - Luminary body/upright tube of special steel painted in any RAL or DB colour without surcharge, or special steel, ground and passivated - All electrical components accommodated on a block -Crown detachable for easy maintenance/lamp change - Upright tube without pole door, incl. adapter jack - Upright tube with pole door, incl. cable joint box for cable 5 x 10 mm2 or 3 cable 5 x 6 mm2 - incl.....Dulux L24W-31-830 SP Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711

## Light output 1



2 x DULUX L-SP			
Nominal lamp power	24 W	LOR	54%
Lamp flux	1800 lm	ULOR	29%
Luminous efficacy	36 lm/W	Total flux	1957 lm
CCT	2899 K	Total power	54 W
CRI	90		

## Mounting mode

Standing / Bollard

## Shape and measurements

Height: 44.49 in  
Diameter: 3.94 in

## Electric

System power: 54 W

## Protection

IP: 55