


Product data sheet

ALPHABET SPECTRA RECESSED LUMINAIRE, DOWNLIGHT
AS1102104-30-27 + 83819R08-WT_6W
SCHMITZ | WILA



alphabet spectra LED 2700 K Recessed Luminaire, Light distribution direct Downlight Reflector white coated Product: AS1102104-30-27
Operating technology: independent driver required Lite Optic: 83819R08-WT Lite Optic Aluminium reflector, coated white Reflector with safety strap for easy installation Half-peak divergence $\alpha = 60^\circ$ Light Technique CRI 83 (typ.) highest colour consistency with 1x2 SDCM (initial), max. 3 SDCM covered by 5 years warranty constant colour temperature 2700 K lifetime 50.000 h (L80/B10); 50.000 h (L70/B0) covered by 5 years warranty Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised ring thickness of only 2 mm for homogeneous appearance in the ceiling ring colour white, RAL 9016 Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 2-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 6 W Colour Rendering Index: 83 Colour Temperature: 2700 K Luminaire Luminous Flux: 560 Lm System Efficiency: 80 Lm/W Half-peak Divergence $\alpha: 60^\circ$ Number Luminaires LZ: 0.24 Connector: plug-in terminal, 7 x 2.5 mm², with loop-in function Reflector Size: R08 Diameter D: 102 mm Cut-out CO: 95 mm Installation Depth RD: 95 mm Degree of Protection IP20 CE-Sign Total system: Protection class 2 Data record AS1102104-30-27+83819R08-WT_6W

Light output 1



1 x General service incandescent lamp			
Nominal lamp power	7 W	LOR	100%
Lamp flux	560 lm	Total flux	560 lm
Luminous efficacy	80 lm/W	Total power	7 W
CCT	2700 K		
CRI	83		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.74 in
Diameter: 4.02 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 7 W
Appliance Class: II

Protection

IP: 20