


Product data sheet

POM OPAL-BOLLARD
7150-0-2-495-XX
UNILAMP



Description POM is the family of unshielded bollard with symmetrical light distribution. High power COB LED is installed inside this luminaire. It is available in 2 color temperature 3000K and 4000K. The impact resistant PC lens cover is available in prismatic and opal, both producing a uniform wide beam light distribution. POM is generally installed in the walk ways, parks, gardens, commercial areas and open spaces where general lighting is needed. We produce the bollard at different height according to the customer design. Anchorage unit for concrete foundation is available as an accessory. Spec • Designed, Manufactured and Tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 Die Cast Aluminium and Extruded Aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Polycarbonate diffuser. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 Terminal block. • Weather proof TPE grommet. • Bollard pre-wired with outdoor cable. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



1 x Compact fluorescent lamp			
Nominal lamp power	23 W	Socket	E27
Lamp flux	1500 lm	LOR	29%
Luminous efficacy	65 lm/W	ULOR	15%
CCT	3000 K	Total flux	440 lm
CRI	84	Total power	23 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 6.89 in
Width: 6.89 in
Height: 36.81 in

Adjustability

Fixed

Electric

System power: 23 W
Appliance Class: II

Protection

IP: 65
IK: 10