



# Product data sheet

PARAGON 2 ON-GROUND UPLIGHT  
PR-50011-N-W40  
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Extruded aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

## Light output 1 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 4032 K |
| Nominal lamp power | 39 W    | CRI         | 80     |
| Total flux         | 3437 lm | LOR         | 100%   |
| Luminous efficacy  | 88 lm/W | ULOR        | 100%   |
|                    |         | Total power | 39 W   |

## Mounting mode

Standing / Bollard, Wall mounted

## Shape and measurements

Height: 11.65 in  
Diameter: 6.30 in  
Weight: 2.2 kg

## Adjustability

Fixed

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 39 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 65  
IK: 08  
Surface temperature: 40°C