

Product data sheet


DOWNTOWN NO TRIM Ø215
03.0461/TC-TEL/2X26W
FLOS



IP
23

Luminaires for embedded installation indoor with fluorescent lamps and of halogenuro metalist. Optical body made in injected aluminium with powder-coated paint finish. Heatsink made in injected aluminium under pressure attached to the body of the luminaire. Lower and upper reflectors available made of anodized aluminium with specular finish. Fixed upper reflector. Inferior reflector formed by self reflector and a spreading lens of 4mm thick and a polycarbonate ring that fixes the reflector to the aluminium ring of the product. Available in two diameters 160mm and 215mm.


Light output 1



2 x Compact fluorescent lamp

Nominal lamp power	26 W
Lamp flux	1800 lm
Luminous efficacy	53 lm/W
CCT	4000 K
CRI	80

Socket	Gx24Q-3
LOR	38%
Total flux	1366 lm
Total power	26 W



2 x Compact fluorescent lamp

Nominal lamp power	26 W
Lamp flux	1800 lm
Luminous efficacy	53 lm/W
CCT	3000 K
CRI	84

Socket	Gx24Q-3
LOR	38%
Total flux	1366 lm
Total power	26 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 7.36 in
Diameter: 7.99 in

Adjustability

Fixed

Electric

System power: 26 W

Protection

IP: 23