


Product data sheet

MIC 1 FLOODLIGHTS,PROJECTORS
MI-50371-M-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 200,000 - Life time L80B10 Ta 50° 490,000 - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	12.5 W	CRI	80
Total flux	1020 lm	LOR	100%
Luminous efficacy	82 lm/W	Total power	12.5 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Height: 10.83 in
Diameter: 5.20 in
Weight: 2.3 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 12.5 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C