# Product data sheet

## LERS4B/LESQS4B LED 4" SHALLOW ROUND AND SQUARE CYLINDERS

IP 47


LE\_4B15D010 EC4B10208040 4LBN1B

COOPER LIGHTING



Mounting: ceiling, wall, stem, aircraft cable; Down or up/down styles, Shallow extruded housing; Die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W<sup>™</sup> option from 3000K to 1850K, Lumens: 1,000-3000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

#### Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	14.3 W	CRI	100
Total flux	697 lm	LOR	100%
Luminous efficacy	49 lm/W	Total power	14.3 W

### Mounting mode

Ceiling recessed

#### Shape and measurements

Length: 3.94 in Width: 3.94 in Height: 3.94 in

#### Adjustability

Fixed

#### Electric

System power: 14.3 W

#### Protection

IP: 47