# Product data sheet

SPIKE BLACK TWILIGHT W/ OUTLET 840LM 3000K RA>80 614921

SG ARMATUREN












Very attractive wall luminaire for outdoor mounting. Comes only as a downlight with good light scattering via the efficient LED module, and a version that also has a small slit as an uplight, which makes high walls look nice. Both variants available with or without two 230 V power points concealed behind two tip-up lids with automatic closure. If you choose the version with connectors, there is a separate terminal strip for the connections. Easy mounting and option of control via integrated dimming relay makes Spike the modern choice for wall lighting. Made of powder-coated aluminium with a 10-year corrosion warranty. Light distribution Direct Light technic LED 11W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs at Ta=25°C Control/Dimming On/Off Protection Class I IP44 IK08 Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: Black (RAL 9004) Optics: Polycarbonat (PC) Mounting/Connection Surface, Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

## Light output 1 (integrated)



Lamp type
Nominal lamp power
Total flux
Luminous efficacy

LED	
11 W	
840 lm	
76 lm/W	

CCT	
CRI	
LOR	
Total power	

3000 K 80 100%

11 W

## Mounting mode

Wall mounted

### Shape and measurements

Length: 6.53 in Width: 6.01 in Height: 6.69 in

# Adjustability

Fixed

# Design

Color of housing: Black

# Electric

System power: 11 W Appliance Class: I

#### Protection

IP: 44 IK: 08