


Product data sheet

LAURA
310100
FLOS



• Outdoor cylindrical bollard light. • Configuration: die-cast aluminium cap EN AB-47100 alloy (low copper content) and extruded aluminium pole • Double layer coating for high resistance to corrosion: The aluminium components are painted with a double coat using powders which are compliant with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents). The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Opal polycarbonate diffuser, silicone gaskets

Light output 1



1 x Halogen low voltage lamp without reflector

Nominal lamp power	150 W	Socket	E27
Lamp flux	2500 lm	LOR	67%
Luminous efficacy	11 lm/W	ULOR	34%
CCT	2800 K	Total flux	1673 lm
CRI	100	Total power	150 W

Mounting mode

Pole top mounted, Standing / Bollard

Shape and measurements

Height: 10.83 in
Diameter: 5.51 in

Adjustability

Fixed

Electric

System power: 150 W
Appliance Class: I

Protection

IP: 54
IK: 08