

Product data sheet


A55-W1200 LED 5600 840
GLAMOX



IP
20

Light source LED 926 mm length LED 4500 - 5800 Lumen out 1226 mm length LED 5600 - 7000 Lumen out Light source information: 3000/4000 Kelvin, CRI 80, CRI 90 on request. 926 mm with CCT on request, MacAdams 3. Lifetime LED: Up to 100.000h Ta25. For precise technical information please see the data sheet on item level. (Use <Find your version> on right hand side) T5 926 mm length Up 2x21/39W Down 1x14/24W 1226 mm length Up 2x28/54W Down 1x14/24W Ballast T5: Electronic ballast (HF) or DALI. LED: DALI Body material & colour Aluminum profile with steel base powder coated Mounting frame in alu-zinc Diffuser up and down in acrylic material resistant to detergents and disinfection liquids. Mounting Surface mounted directly to the wall. Connection 3/5 pole push-in terminal block ready for through wiring. Electrical connection in center of the luminaires as standard, asymmetrical electrical connection is available on request.

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 66 W | CRI | 80 |
| Total flux | 5648 lm | LOR | 100% |
| Luminous efficacy | 86 lm/W | ULOR | 87% |
| | | Total power | 66 W |

Mounting mode

Wall mounted

Electric

System power: 66 W

Shape and measurements

Length: 48.27 in
Width: 7.52 in
Height: 3.74 in

Protection

IP: 20

Adjustability

Fixed