


Product data sheet

PETRA 1 IN-GROUND LUMINAIRES
PET-60001-N-W40
LIGMAN



- Lamp MR16-GU10 - Colour 3000K , 4000K - Casting brass housing - 6 mm thick front ring in brass - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, 10 mm thick, toughened glass - Integral control gear - Recessing box in high-density polyethylene is included - Suitable for walk-over with a maximum load of 200 kg

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	7.5 W	CRI	80
Total flux	424 lm	LOR	100%
Luminous efficacy	57 lm/W	ULOR	100%
		Total power	7.5 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 5.91 in
Diameter: 4.72 in
Weight: 2.2 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 7.5 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 67
IK: 10
Surface temperature: 40°C