# Product data sheet

MAR 10 STREET AND AREA LIGHTING LUMINAIRES MA-97092-W-W40

LIGMAN










- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Surge protection 10kV

### Light output 1 (integrated)



Lamp type	L
Nominal lamp power	53.5
Total flux	6421
Luminous efficacy	120 lm

LED	CCT
53.5 W	CRI
6421 lm	LOR
20 lm/W	Total power

4032	ŁΚ
8	80
100	)%
53.5	W

# Mounting mode

Wall mounted, Pole top mounted

#### Shape and measurements

Height: 10.24 in Diameter: 17.24 in Weight: 15.8 kg

# Adjustability

Fixed

#### Design

Color of housing: Black, White, Silver gray

### Glare protection

Glare protection: UGR < 19

#### Electric

System power: 53.5 W Voltage: 230 V AC Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

# Protection

IP: 55 IK: 07

Surface temperature: 40°C