

Product data sheet


O15-S210 LED 1200 840
GLAMOX



IP
65

Light source LED 1200 lumen out Colour tolerances: MacAdams 3 Colour rendering: CRI 80 Lifetime: Minimum 50 000 hours, L70 For precise lumen values please see the data sheet on item level Ballast Fixed output (HF) or DALI dimmable (100-1%). Body material & colour Manufactured with housing made of die-cast aluminium. Double layer polyester powder coated paint finish in 4 different colours; black, white, anthracite or aluminium grey. The diffuser is made of impact resistant opal acrylic. Supplied with silicon gasket and screws in stainless steel. Mounting Installation directly on the ceiling or wall. Accessories Set of two pcs. M20 cable glands for through wiring. Connection Cable inlet through membrane gland (cable Ø8-13 mm) on the backside of the luminaire. 3 pole (HF) or 5 pole (DALI) 2,5 mm² screw terminal block in the luminaire housing. Through wiring from the side is possible by drilling two holes for M20 cable glands. Outdoor use requires suitable flexible cables assuring the water tightness of the membrane gland.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	18 W	CRI	80
Total flux	1260 lm	LOR	100%
Luminous efficacy	70 lm/W	ULOR	13%
		Total power	18 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.50 in

Diameter: 8.27 in

Adjustability

Fixed

Electric

System power: 18 W

Protection

IP: 65