



Product data sheet

FLAT BASIC
211399.002.1.76
RZB



Series: FLAT BASIC Decorative round surface-mounted luminaire. Base: plastic. Mouth blown 3-layer opal glass (Triplex glass) with satin finish. Diffuser fastening: spring system. Triplex glass produces particularly homogeneous, soft and glare free lighting. Suitable for ceiling mounting, wall (surface). Colour: pure white (RAL#160;9010) Diameter: 370#160;mm Height: 118#160;mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 83 System power: 13#160;W Rated luminous flux: 1150#160;lm Luminous efficiency: 88#160;lm/W Control gear: AC power, DALI dimmable Protection class: I Type of protection: IP#160;43

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1150 lm	LOR	100%
Luminous efficacy	88 lm/W	ULOR	15%
		Total power	13 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.65 in
Diameter: 14.57 in

Adjustability

Fixed

Design

Material impression: Matt
Color of housing: Black

Electric

System power: 13 W
Ballast: ECG

Protection

IP: 43
IK: 02
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 32...95°F