Product data sheet

NADJA IV (WALL FITTING) 9.847.2152.05

LEIPZIGER LEUCHTEN








Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded -Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1




1 x High pressure sodium vap	our lamp
Nominal lamp power	50 W
Lamp flux	2500 lm

Lamp flux 3500 lm 44 lm/W Luminous efficacy CCT 2000 K CRI

LOR 78% Total flux 2737 lm Total power 62 W

25



1 x High pressure sodium vapour lamp

CRI

Nominal lamp power 70 W LOR 78% Lamp flux 5600 lm Total flux 4379 lm Luminous efficacy 53 lm/W Total power 83 W CCT 2000 K

Mounting mode

Wall mounted

Shape and measurements

Height: 16.54 in Diameter: 16.54 in

Design

Material impression: Matt

Glare protection

25

Glare protection: UGR < 19

Electric

System power: 62-83 W

Ballast: ECG

Protection

IP: 55

Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: 32...95°F