


Product data sheet

FLEX STRIP IP68 800 HE+ MONO - UWW
L685936HL
PROLED (MBN GMBH)



The PROLED FLEX STRIPS are perfect for indirect lightning, as custom made versions for fair or shop applications as well as for all kinds of illumination. Due to their shallow design and the individually adaptable lengths the PROLED FLEX STRIPS offer a wide spectrum of application possibilities. - High efficiency - High flexibility - adaptable to round shapes. - Installation with clamps or special glue. The 3M adhesive tape on the strip's backside (self adhesive) is only as fit-up aid. - IP68 for under water use (power supply cable/end caps IP65 when correctly sealed. - dimmable and controllable via DMX 512, DALI, KNX, 1-10V, CASAMBI, RF by MULTI power supplies/controller

Light output 1 (integrated)



Lamp type	LED	CCT	2400 K
Nominal lamp power	20 W	CRI	90
Total flux	1700 lm	LOR	100%
Luminous efficacy	85 lm/W	Total power	20 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 39.37 in

Width: 0.51 in

Height: 0.24 in

Adjustability

Fixed

Electric

System power: 20 W

Controller: Dimmable 1..10V, DMX, DALI

Appliance Class: III

Protection

IP: 68

Other operating numbers

Ambient temperature range: 14...113°F