

Product data sheet

SPL L45 E3
SPLASH LED EMERGENCY
DEXTRA




IP
65




Splash LED - 1500mm, IP65 Corrosive resistant luminaire, with pressed stainless steel body and toughened polycarbonate diffuser. Options: E3 - Emergency control gear (480 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) Available with glass cover on request

Light output 1 (integrated, emergency)



Lamp type		CCT	3783 K
Nominal lamp power	3 W	CRI	80
Total flux	479 lm	LOR	100%
Luminous efficacy	160 lm/W	Total power	3 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	26 W	CRI	80
Total flux	2774 lm	LOR	100%
Luminous efficacy	107 lm/W	Total power	26 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 4.96 in

Width: 4.96 in

Height: 5.08 in

Adjustability

Fixed

Electric

System power: 29 W

Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 65