


# Product data sheet

GANDALF 26 FLOODLIGHTS,PROJECTORS  
GA-51088-T2-W40  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Through wiring on request - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Hot-dipped galvanised steel mounting bracket allows for ceiling, wall or surface mounting - Integral control gear

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.5 W	CRI	80
Total flux	4956 lm	LOR	100%
Luminous efficacy	132 lm/W	Total power	37.5 W

## Mounting mode

Standing / Bollard, Wall mounted

## Shape and measurements

Height: 16.69 in  
Diameter: 11.81 in  
Weight: 8.5 kg

## Adjustability

Free

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 37.5 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 66  
IK: 08  
Surface temperature: 40°C