

Product data sheet

PAULA VII
9.647.3066.05
LEIPZIGER LEUCHTEN



IP
55

Recommended mounting height 4.50 - 6.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Easy installation with adapter jack - Available in any RAL or DB colour without surcharge - Scope of supply includes painted special steel brackets - please order pole dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711
Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	41 lm/W
CCT	3400 K
CRI	54

LOR	83%
Total flux	5651 lm
Total power	137 W



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W
Lamp flux	4000 lm
Luminous efficacy	37 lm/W
CCT	3400 K
CRI	54

LOR	83%
Total flux	3324 lm
Total power	89 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.74 in

Diameter: 28.74 in

Electric

System power: 89-137 W

Protection

IP: 55