


Product data sheet

DINO APOLLO WHITE ALU 3K - DALI
53778-402
FAGERHULT



Installation Two point suspension c/c 150 mm. Connection 230 V integrated LED ballast. Snap-in terminal block 5x2.5 mm². 1-phase through-wiring possible. Surface mounted mains cable possible 180°. Design Luminaire body of aluminium in white (RAL 9016) or graphite grey textured enamel. Ø 300 – supplied with 3,0 m white fabric cord 5x0,75 mm² and white, plastic ceiling cup. Ø 500 – supplied with 4,0 m white fabric cord 5x0,75 mm², 4,0 m wire suspension with friction locks for height adjustment and white, plastic ceiling cup. Dimming DALI/phase-pulse control as standard. Miscellaneous Luminaire 300 mm has a switch for high/low flow. Always delivered set at high flow and need to be adjusted for low flow.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	80 W	CRI	80
Total flux	6677 lm	LOR	100%
Luminous efficacy	83 lm/W	Total power	80 W

Mounting mode

Pendant

Electric

System power: 80 W

Shape and measurements

Length: 19.69 in
Width: 19.69 in
Height: 16.99 in

Protection

IP: 20

Adjustability

Fixed

Design

Color of housing: White