


# Product data sheet

TOLDBOD 290 POST LED 4000K 20W CLO  
5747811528  
LOUIS POULSEN



Tolddbod 290 Post Design by: Louis Poulsen Concept : The light is directed 100% downwards and the shade has a matt white painted interior emitting a soft, diffused, comfortable light. Finish: Aluminium coloured with textured surface or black with textured surface, powder coated. Materials: Fixture head: Die cast aluminium. Shield: Injection moulded clear polycarbonate. Pole top: Galvanized, steel. Mounting: Pole dimension: Ø 48mm or Ø 60mm. Installation cable: 3,5m 2x1mm² (-DPC Cl.I), 3,5m 3x1mm² (-DPC Cl.I), 3,5m 4x1mm² (-DAC Cl.II), 3,5m 5x1mm² (-DAC Cl.I). Driver: In fixture head. Class: Ingress protection IP65. Electric shock protection I w. ground, II w/o ground. IK08. Sizes and weights: Width x Height x Length (mm) 290 x 300 x 475 Max 10.1 kg

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	80
Total flux	1987 lm	LOR	100%
Luminous efficacy	99 lm/W	Total power	20 W

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 11.81 in

Diameter: 11.42 in

## Adjustability

Fixed

## Electric

System power: 20 W

Appliance Class: I

## Protection

IP: 65

IK: 08