

# Product data sheet

MULTILUME FLAT OPAL VTB 4000K DALI CLO  
23910-520  
FAGERHULT



Installation Recessed mounting in ventilated or unventilated suspended ceilings. Two optional designs. VTB - for suspended ceilings with visible T-bars 25 mm. 300x300 also for fixed suspended ceilings. HB - for suspended ceiling with concealed T-bars. Supplement with fixing brackets for fixed suspended ceiling, see accessories. The luminaire must not be covered with insulation. For further details please refer to the assembly instructions on our website. Connection Connection in ballast box. The ballast box can be detached and positioned next to the luminaire. Snap-in terminal block 3x1,5?mm² (5x1,5?mm² where dimming is required). Through-wiring possible for 600x600. Design Luminaire body in white enamelled sheet steel (RAL 9016). Louvre Opal - Opal plate in frosted acrylic (PMMA). Miscellaneous Enclosure class IP 44 under suspended ceilings and IP 20 above suspended ceilings.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	34 W	CRI	80
Total flux	4234 lm	LOR	100%
Luminous efficacy	125 lm/W	Total power	34 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 47.09 in

Width: 11.65 in

Height: 2.68 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 34 W

## Protection

IP: 44