



Product data sheet

WALL MOUNTED LUMIN. RESIDENZA 4000K
10.10951.0VXXX + 10.40900.0V001
HESS




Protective cover made of aluminium. Luminaire rests on four aluminium rods, concealed by design sheet. Cylindrical luminaire body made of cast aluminium, universal holder for poles with spigot 60.3 - 82.5 mm. Luminaire enclosure made of PMMA, clear. Diameter 200mm.
10.40900.0V001 Wall bracket RESIDENZA Made of aluminium Overhanging: 300 mm Colour: DB 703 or all RAL- (classic- single shades), Hess-DB and Hess-Glimmer-colours. RAL pearl-mica-metallic-shades on request.


Light output 1




1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3173 lm	Total flux	3173 lm
Luminous efficacy	113 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3023 lm	Total flux	3023 lm
Luminous efficacy	108 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	28 W	LOR	100%
Lamp flux	3161 lm	Total flux	3161 lm
Luminous efficacy	113 lm/W	Total power	28 W
CCT	4000 K		
CRI	80		


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

28 W
3167 lm
113 lm/W
4000 K
80

LOR
Total flux
Total power

100%
3167 lm
28 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2387 lm
119 lm/W
4000 K
80

LOR
Total flux
Total power

100%
2387 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2273 lm
114 lm/W
4000 K
80

LOR
Total flux
Total power

100%
2273 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2383 lm
119 lm/W
4000 K
80

LOR
Total flux
Total power

100%
2383 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

20 W
2386 lm
119 lm/W
4000 K
80

LOR
Total flux
Total power

100%
2386 lm
20 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

15 W
1671 lm
111 lm/W
4000 K
80

LOR
Total flux
Total power

100%
1671 lm
15 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

15 W
1591 lm
106 lm/W
4000 K
80

LOR
Total flux
Total power

100%
1591 lm
15 W


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

15 W
1668 lm
111 lm/W
4000 K
80

LOR
Total flux
Total power

100%
1668 lm
15 W

**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

15 W
1670 lm
111 lm/W
4000 K
80

LOR
Total flux
Total power

100%
1670 lm
15 W

Mounting mode

Wall mounted, Pole top mounted, Pole integrated

Shape and measurements

Length: 15.37 in
Width: 8.03 in
Height: 31.12 in

Adjustability

Tiltable

Electric

System power: 15-28 W

Protection

IP: 65