


Product data sheet

ELLBD 12L40 LE3
ELEMENT EMERGENCY
DEXTRA




Element - 1200mm Suspended bi-directional luminaire, white powder coated steel body with low glare microprism diffuser. Can be continuous run. Options: LE3 - Lithium Emergency (333 lumens output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)* H - High Frequency Dimming (Analogue 1-10v) R44 - Daylight regulating and Occupancy Sensor RAS - Reacta Air Wireless occupancy and daylight dimming B - Black Body GY - Grey Body Continuous Run options: ST - Start of Run TW - Through Wire ER - End of Run ELL COR TW - Element Adjustable Through Wire Corner ELL BLIND 1260 TW - Element Suspended Continuous Run, 1260mm, 6 pole through wire blind unit ELL BLIND 1500 TW - Element Suspended Continuous Run, 1500mm, 6 pole through wire blind unit ELL EC - Element End Cap (please specify one set per run of luminaires). ELL JOINER - Element Joining Kit (required to connect End of Run to Start of Run luminaires where new power feeds are required mid run) P414 - 3M Suspension Kit

Light output 1 (integrated, emergency)




| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | | CCT | 4000 K |
| Nominal lamp power | 3 W | CRI | 80 |
| Total flux | 596 lm | LOR | 100% |
| Luminous efficacy | 199 lm/W | Total power | 3 W |

Light output 2 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | | CCT | 4000 K |
| Nominal lamp power | 13.4 W | CRI | 80 |
| Total flux | 1674 lm | LOR | 100% |
| Luminous efficacy | 125 lm/W | ULOR | 100% |
| | | Total power | 13.4 W |

Light output 3 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | | CCT | 4000 K |
| Nominal lamp power | 15.1 W | CRI | 80 |
| Total flux | 1677 lm | LOR | 100% |
| Luminous efficacy | 111 lm/W | Total power | 15.1 W |

Mounting mode

Pendant

Shape and measurements

Length: 49.61 in

Width: 9.06 in

Height: 1.61 in

Adjustability

Fixed

Electric

System power: 31.5 W

Ballast: ECG

Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20

Designation labels: CE