


# Product data sheet

PH 5-4½ E27 LED 2700K 21W  
5741085868  
LOUIS POULSEN



PH 5-4½ & PH 6½-6 Design : Poul Henningsen Concept : The trumpet-shaped top shade on the fixture provides illumination of the area above the three shades, which primarily direct the light downwards. A base reflector and a blue glare ring protect against glare from all angles. The strongest light is directly under the fixture. The shades have a matte white painted finish to ensure very comfortable lighting. Finish : White. Material : Shades: Spun aluminium. Anti-glare disc: Blue, spun aluminium. Struts: Rolled aluminium coloured. Mounting : Suspension type: Cable 3x0,75mm² or cable 3x0,75mm² & wire. Canopy: Yes. Cable length: PH 5-4½: 3m, PH 6½-6: 4m. Class : Ingress protection IP20. Electric shock protection I w. ground. Weight : Max. 6kg.

## Light output 1



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| 1 x LED            |         |             |        |
| Nominal lamp power | 21 W    | LOR         | 32%    |
| Lamp flux          | 2500 lm | ULOR        | 2%     |
| Luminous efficacy  | 38 lm/W | Total flux  | 790 lm |
| CCT                | 2700 K  | Total power | 21 W   |
| CRI                | 80      |             |        |

## Mounting mode

Pendant

## Shape and measurements

Height: 12.52 in  
Diameter: 18.35 in  
Weight: 0.3 kg

## Adjustability

Fixed

## Electric

System power: 21 W  
Appliance Class: I

## Protection

IP: 20  
Designation labels: CE