Product data sheet

SMART KUP 160 IP55 LED GE 2700K SPOT BLACK STRUC 13024032


MODULAR







Subtle lighting Smart kup is one of the 3 forms of the Smart family. The cone of the Smart kup ends in a fine trim. A trim particular Modular. The same subtle trim is used in several other Modular luminaires. The Smart family's styling is based on our most popular designs. Concretely this means that the luminaires consist of a light source (LED or halogen) which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing. Also available in different sizes, fix and adjustable, IP version, ...


Light output 1









1 x LED			
Nominal lamp power	36.3 W	LOR	90%
Lamp flux	3949 lm	Total flux	3545 lm
Luminous efficacy	98 lm/W	Total power	36.3 W
CCT	2700 K		
CRI	90		
1 x LED			
Nominal lamp power	30.8 W	LOR	90%
Lamp flux	3415 lm	Total flux	3065 lm
Luminous efficacy	100 lm/W	Total power	30.8 W
CCT	2700 K		
CRI	90		
1 x LED			
Nominal lamp power	23.5 W	LOR	90%
Lamp flux	2751 lm	Total flux	2469 lm
Luminous efficacy	105 lm/W	Total power	23.5 W
CCT	2700 K		
CRI	90		







1 x LED Nominal lamp power LOR 90% 16 W Lamp flux Total flux 1813 lm 2020 lm Luminous efficacy 113 lm/W Total power 16 W CCT 2700 K CRI 90 1 x LED Nominal lamp power 49.7 W LOR 90% Lamp flux 5107 lm Total flux 4584 lm Luminous efficacy 92 lm/W Total power 49.7 W CCT 2700 K CRI 90 1 x LED Nominal lamp power 42 W LOR 90% Lamp flux 4436 lm Total flux 3982 lm Luminous efficacy 95 lm/W Total power 42 W CCT 2700 K CRI 90

Mounting mode

Ceiling recessed

Shape and measurements

Length: 6.30 in Width: 6.30 in Height: 5.08 in Weight: 0.91 kg

Adjustability

Fixed

Electric

System power: 16-49.7 W Appliance Class: II

Protection

IP: 55