

Product data sheet

KERALUX
59250.002
RZB




IP
40

IK
04

Series: Keralux Type of Protection: IP 40 Protection Class: II Voltage: - 250 / 0 - 60 Hz Base: ceramic, with integrated E27 lampholder. Glass fastening: screw fitting, D 84.5mm. One lateral cable inlet: PG13.5. IP54 only in conjunction with glass cover. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 125, H 50 Lamp: 1 x E27 max. 100 W Socket 1: E27 Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK04 (0,50 Joule) Beam Angle: 180° Unified Glare Ratio: 18,7 EEC: A++ - E

Light output 1



1 x Compact fluorescent lamp

Nominal lamp power	15 W	Socket	E27
Lamp flux	970 lm	LOR	90%
Luminous efficacy	58 lm/W	ULOR	44%
CCT	2700 K	Total flux	873 lm
CRI	80	Total power	15 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 14.17 in
Diameter: 4.92 in

Adjustability

Fixed

Electric

System power: 15 W

Protection

IP: 40
IK: 04