


# Product data sheet

SPL L35 E3  
SPLASH LED EMERGENCY  
DEXTRA




Splash LED - 1500mm, IP65 Corrosive resistant luminaire, with pressed stainless steel body and toughened polycarbonate diffuser. Options: E3 - Emergency control gear (480 lumens output) ST3 - Emergency Selftest AT3 - Emergency Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) Available with glass cover on request

## Light output 1 (integrated, emergency)



Lamp type		CCT	3783 K
Nominal lamp power	3 W	CRI	80
Total flux	479 lm	LOR	100%
Luminous efficacy	160 lm/W	Total power	3 W

## Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	18.6 W	CRI	80
Total flux	2163 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	18.6 W

## Mounting mode

Ceiling mounted, Contact rail

## Shape and measurements

Length: 62.99 in

Width: 5.47 in

Height: 4.06 in

## Adjustability

Fixed

## Electric

System power: 21.6 W

Ballast: ECG

Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 65

Designation labels: CE