


# Product data sheet

LUCAS III (WALL FITTING BEADED)  
9.837.1032.16  
LEIPZIGER LEUCHTEN



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	83%
Lamp flux	7200 lm	ULOR	2%
Luminous efficacy	67 lm/W	Total flux	5968 lm
CCT	3000 K	Total power	89 W
CRI	90		

## Mounting mode

Wall mounted

## Shape and measurements

Height: 22.44 in  
Diameter: 22.44 in

## Design

Material impression: Matt  
Color of housing: White

## Electric

System power: 89 W  
Ballast: ECG

## Protection

IP: 55  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...95°F