Product data sheet

LUCAS IV (WALL FITTING) 9.834.3066.15

LEIPZIGER LEUCHTEN









Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



| 1 x High pressure mercury vapour lamp | | |
|---------------------------------------|---------|--|
| Nominal lamp power | 125 W | |
| Lamp flux | 6800 lm | |
| Luminous efficacy | 42 lm/W | |
| CCT | 3400 K | |
| CRI | 54 | |

| LOR | 84% |
|-------------|---------|
| Total flux | 5697 lm |
| Total power | 137 W |
| | |



| I x High pressure mercury vapour lamp | | | | |
|---------------------------------------|---------|-------------|---------|--|
| Nominal lamp power | 80 W | LOR | 84% | |
| Lamp flux | 4000 lm | Total flux | 3351 lm | |
| Luminous efficacy | 38 lm/W | Total power | 89 W | |
| CCT | 3400 K | | | |
| CRI | 54 | | | |

Mounting mode

Wall mounted

Shape and measurements

Height: 22.44 in Diameter: 22.44 in

Design

Material impression: Matt Color of housing: White Electric

System power: 89-137 W

Ballast: ECG

Protection

IP: 55

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...95°F