


Product data sheet

MONDANA-A
551091.002
RZB



Series: Mondana Type of Protection: IP 65 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: plastic, microtextured finish. Diffuser fastening: screw fitting. Diffuser: hand-blown opal glass, satin finish. With Gore-TM Protective Vents membrane valve as standard. Available Colours: pure white (RAL 9010) Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 390, H 101 Lamp: LED Life time: 50000 h (L80/B50) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 1000lm System power: 13W Beam Angle: 116° Number of fittings B10A: 114 Number of fittings B16A: 182 Number of fittings C10A: 114 Number of fittings C16A: 182 Inrush current: 0,15A Unified Glare Ratio: 17,6 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1000 lm	LOR	100%
Luminous efficacy	77 lm/W	ULOR	14%
		Total power	13 W

Mounting mode

Wall mounted

Shape and measurements

Height: 3.98 in
Diameter: 15.35 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 13 W

Protection

IP: 65
IK: 03