


Product data sheet

PIANO 2000 GRAPHITE 1500LM 3000K RA>80 TRAILING EDGE DIMMING
7021986338768
SG ARMATUREN



Design: Svein Knudsen / Andrew Smith Attractive, round luminaire with indirect light that can be mounted to both walls and ceilings, both indoors and outdoors. Made of die-cast powdercoated aluminium. Flat diffuser made of UV-stabilised opal polycarbonate. Efficient and powerful with several light source variants and option of both sensor and wireless control. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Corrosion-proof with 10-year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct/Indirect Light technic LED 14W 3000K Ra>80 SDCM 3 L70/B50 >100,000 hrs Control/Dimming Trailing edge dimming Protection Class I IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: Graphite Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Outdoor Screwless terminal block

Light output 1



1 x LED			
Nominal lamp power	14 W	LOR	100%
Lamp flux	1500 lm	ULOR	6%
Luminous efficacy	107 lm/W	Total flux	1500 lm
CCT	3000 K	Total power	14 W
CRI	80		

Mounting mode

Wall mounted

Shape and measurements

Length: 13.39 in

Width: 3.94 in

Height: 13.39 in

Adjustability

Fixed

Electric

System power: 14 W

Appliance Class: I

Protection

IP: 65

IK: 10