

Product data sheet


NOMAD 111 2X LED 2700K FLOOD GE
1202320X
MODULAR




IP
20

Timeless passe-partout Nomad is a classic. This refined, industrial fitting with its visible wiring is perfect for highlighting your favourite elements in your interior. The family comprises a wide range of lighting solutions. For example, the flexible arm allows Nomad to travel a certain distance.


Light output 1



| | | | |
|--------------------|---------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 23.6 W | LOR | 100% |
| Lamp flux | 1625 lm | Total flux | 1623 lm |
| Luminous efficacy | 69 lm/W | Total power | 23.6 W |
| CCT | 2700 K | | |
| CRI | 90 | | |




| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 11 W | LOR | 100% |
| Lamp flux | 920 lm | Total flux | 919 lm |
| Luminous efficacy | 84 lm/W | Total power | 11 W |
| CCT | 2700 K | | |
| CRI | 90 | | |




| | | | |
|--------------------|---------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 16.25 W | LOR | 100% |
| Lamp flux | 1256 lm | Total flux | 1254 lm |
| Luminous efficacy | 77 lm/W | Total power | 16.25 W |
| CCT | 2700 K | | |
| CRI | 90 | | |


Light output 2



| | | | |
|--------------------|---------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 23.6 W | LOR | 100% |
| Lamp flux | 1625 lm | Total flux | 1623 lm |
| Luminous efficacy | 69 lm/W | Total power | 23.6 W |
| CCT | 2700 K | | |
| CRI | 90 | | |



| | | | |
|--------------------|---------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 11 W | LOR | 100% |
| Lamp flux | 920 lm | Total flux | 919 lm |
| Luminous efficacy | 84 lm/W | Total power | 11 W |
| CCT | 2700 K | | |
| CRI | 90 | | |



| | | | |
|--------------------|---------|-------------|---------|
| 1 x LED | | | |
| Nominal lamp power | 16.25 W | LOR | 100% |
| Lamp flux | 1256 lm | Total flux | 1254 lm |
| Luminous efficacy | 77 lm/W | Total power | 16.25 W |
| CCT | 2700 K | | |
| CRI | 90 | | |

Mounting mode

Ceiling mounted

Shape and measurements

Length: 12.64 in
Width: 6.69 in
Height: 7.32 in
Weight: 1.64 kg

Adjustability

Tiltable

Electric

System power: 22-47.2 W

Protection

IP: 20