Product data sheet

SMART KUP 115 LED GE 3000K SPOT BLACK STRUC 12761432


MODULAR







Smart lighting family Smart Cake, Smart Lotis and Smart Kup form a new generation of spotlights which combine technical ingenuity with timeless design. This family's styling is based on our most popular designs. In concrete terms, the fittings consist of a module which can be combined with one of three trims to suit your requirements. The new spotlights can be combined with Smart Mask or Smart surface box to form the perfect solution for any interior. What you get is a LED module with a different finish. The design of the Smart Kup looks like a flaring cylinder.

Light output 1







Mounting mode

Ceiling recessed

I x LEDLOR97%Lamp flux1908 lmTotal flux1856 lmLuminous efficacy79 lm/WTotal power23.6 WCCT3000 K23.6 W23.6 WCRI909050.00000000000000000000000000000000000	1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	11 W 1046 lm 93 lm/W 3000 K 90	LOR Total flux Total power	97% 1018 lm 11 W
Nominal lamp power23.6 WLOR97%Lamp flux1908 lmTotal flux1856 lmLuminous efficacy79 lm/WTotal power23.6 WCCT3000 K70 lm/WTotal powerCRI909090I x LEDNominal lamp power16.25 WLORLamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 K1625 W1625 W				
Nominal lamp power23.6 WLOR97%Lamp flux1908 lmTotal flux1856 lmLuminous efficacy79 lm/WTotal power23.6 WCCT3000 K70 lm/WTotal powerCRI909090I x LEDNominal lamp power16.25 WLORLamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 KTotal power16.25 W				
Nominal lamp power23.6 WLOR97%Lamp flux1908 lmTotal flux1856 lmLuminous efficacy79 lm/WTotal power23.6 WCCT3000 K70 lm/WTotal powerCRI909090I x LEDNominal lamp power16.25 WLORLamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 K1625 W1625 W	1 x I FD			
Lamp flux1908 lmTotal flux1856 lmLuminous efficacy79 lm/WTotal power23.6 WCCT3000 K70 lm/W70 lm/WCRI909090 lm/WI x LEDNominal lamp power16.25 WLOR97%Lamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 KTotal power16.25 W		23.6 W	LOR	97%
Luminous efficacy79 lm/WTotal power23.6 WCCT3000 K90CRI90I x LEDNominal lamp power16.25 WLOR97%Lamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 K16.25 W16.25 W		1908 lm	Total flux	1856 lm
CRI90 1 x LED LORNominal lamp power16.25 WLamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WCCT3000 K		79 lm/W	Total power	23.6 W
1 x LEDNominal lamp power16.25 WLOR97%Lamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 K500 K500 K	ССТ	3000 K		
Nominal lamp power16.25 WLOR97%Lamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 K500 K500 K	CRI	90		
Nominal lamp power16.25 WLOR97%Lamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 K500 K500 K				
Nominal lamp power16.25 WLOR97%Lamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 K500 K500 K				
Nominal lamp power16.25 WLOR97%Lamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 K500 K500 K				
Lamp flux1434 lmTotal flux1395 lmLuminous efficacy86 lm/WTotal power16.25 WCCT3000 K500 K500 K				
Luminous efficacy86 lm/WTotal power16.25 WCCT3000 K				
CCT 3000 K				
	-		Total power	16.25 W
CRI 90				
	CRI	90		

Shape and measurements

Height: 0.39 in Diameter: 4.53 in

Adjustability

Fixed

Electric

System power: 11-23.6 W Appliance Class: II

Protection

IP: 20