


Product data sheet

VERANDA 5 PILLAR LIGHT LUMINAIRES
VR-70302-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, UV-stabilised polycarbonate lens - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	15.7 W	CRI	80
Total flux	771 lm	LOR	100%
Luminous efficacy	49 lm/W	ULOR	22%
		Total power	15.7 W

Mounting mode

Standing / Bollard

Shape and measurements

Height: 6.30 in
Diameter: 6.30 in
Weight: 1.7 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 15.7 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 67
IK: 08
Surface temperature: 40°C