

Product data sheet

FLAT POLYMERO
311923.002.4.76
RZB




IP
40

IK
10

Series: FLAT POLYMERO Decorative round LED pendant luminaire. Base and canopy: metal, powder-coated, white. Canopy Ø 205 mm, h 35 mm. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for pendant. 3-point steel cable suspension, steplessly adjustable. Special lengths available on request. Colour: white Diameter: 620 mm Height: 160 mm Suspension length: 350-1300 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 28 W Rated luminous flux: 3200 lm Luminous efficiency: 114 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	28 W	CRI	80
Total flux	3200 lm	LOR	100%
Luminous efficacy	114 lm/W	ULOR	8%
		Total power	28 W

Mounting mode

Pendant

Electric

System power: 28 W

Shape and measurements

Height: 6.30 in
Diameter: 24.41 in

Protection

IP: 40
IK: 10

Adjustability

Fixed