## Product data sheet

LSRS8B/LSRSWM8B LED 8" SHALLOW ROUND CYLINDERS LSR8B60D010 EC8B60927 8LBS0LI

COOPER LIGHTING








Mounting: high bay/low bay ceiling, wall, stem or aircraft cable, Spun aluminum housing; Spun aluminum reflectors, 5 color temperatures: 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-6,000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

## Light output 1 (integrated)



Lamp type
Nominal lamp power
Total flux
Luminous efficacy

LED	CCT
59.5 W	CRI
5507 lm	LOR
93 lm/W	Total power

3000	k
10	C
1009	2/
59.5 V	١

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in Width: 3.94 in Height: 3.94 in

Adjustability

Fixed

Electric

System power: 59.5 W

Protection

IP: 47