

# Product data sheet

GUSTAV I (1-ARMED)  
9.681.3046.07  
LEIPZIGER LEUCHTEN



IP  
55


Mounting height of 3.00 to 4.50 m for medium light requirements - Impact-resistant clear polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Aluminium reflector finished in special white paint for max. light reflection - Aluminium cover painted - Unit carrier made of corrosion-resistant cast aluminium, painted - All electrical components arranged on a block - Connection with adapter jack - Available in any RAL or DB colour without surcharge - Order pole, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



### 1 x High pressure mercury vapour lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 50 W    | LOR         | 54%     |
| Lamp flux          | 2000 lm | ULOR        | 11%     |
| Luminous efficacy  | 18 lm/W | Total flux  | 1073 lm |
| CCT                | 3400 K  | Total power | 59 W    |
| CRI                | 54      |             |         |



### 1 x High pressure mercury vapour lamp

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 80 W    | LOR         | 54%     |
| Lamp flux          | 4000 lm | ULOR        | 11%     |
| Luminous efficacy  | 24 lm/W | Total flux  | 2146 lm |
| CCT                | 3400 K  | Total power | 89 W    |
| CRI                | 54      |             |         |

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 29.13 in  
Diameter: 9.84 in

## Electric

System power: 59-89 W

## Protection

IP: 55