


# Product data sheet

JUNISTAR ISOSAFE DINTOWARM WHITE 550LM 2000-2800K RA>95  
901231  
SG ARMATUREN



Attractive downlight for indoor use with 30° 360° stepless tilt. Mounted directly in insulation. Well integrated LED chip with DimToWarm 2800K–2000K via phase-dimming or DALI driver (optional). Made of die-cast powder-coated aluminium or brushed steel, glass diffuser. 42-degree scattering angle via reflector. Low recessed downlight with Ø83 hole dimensions. Tool-free mounting in mounting box for direct 230 V with loopable quick clips and automatic strain relief. IP44. Light distribution Direct Light technic LED (not exchangeable) 8W 2000-2800K Ra>95 SDCM 3 L80/B20 >50,000 hrs at Ta=25°C Control/Dimming Trailing edge dimming Protection Class II SELV IP44 Energy and approvals A++ CE Materials and finish Housing: Aluminium Colour: Matt White (RAL 9003) Optics: Glass Mounting/Connection Recessed, Indoor Screwless terminal block

## Light output 1 (integrated)



Lamp type	LED	CCT	2800 K
Nominal lamp power	8 W	CRI	95
Total flux	550 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	8 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 3.70 in

Width: 3.70 in

Height: 2.20 in

## Adjustability

Tiltable

## Design

Color of housing: White

## Electric

System power: 8 W

Appliance Class: II

## Protection

IP: 44