

Product data sheet

FLAT POLYMERO
311526.002.6.19
RZB




IP
40

IK
10

Series: FLAT POLYMERO Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). With integrated HF movement sensor. HF detector 5.8 GHz ISM frequency band. Sensitivity/Range: 1-8 m in diameter, adjustable from 20-100%. Time control 1 second to 15 minutes in 8 different levels. Coverage: 120°. Can be used as master luminaire up to 800 W (ohmic load), 500 W (fluorescent lamp, LED) / 400 A, 200 µs. Suitable for outdoor use to a limited extent only, as it is sensitive to all movements. Colour: white Diameter D: 620 mm Height H: 160 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI):80 System power 1: 24 W Rated luminous flux 1: 2650 lm Luminous efficacy: 110 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2650 lm	LOR	100%
Luminous efficacy	110 lm/W	ULOR	7%
		Total power	24 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 6.30 in

Diameter: 24.41 in

Adjustability

Fixed

Electric

System power: 24 W

Protection

IP: 40

IK: 10