


Product data sheet

LIGHT LINEAR VT 5 STREET AND AREA LUMINAIRES
VT-20022-T3-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K ,4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket and clear toughened glass - Maximum wind load resistance is 120 km/h - Surge protection 10 kV

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	81.2 W	CRI	80
Total flux	5738 lm	LOR	100%
Luminous efficacy	71 lm/W	Total power	81.2 W

Mounting mode

Pole integrated

Shape and measurements

Length: 3.54 in
Width: 5.91 in
Height: 20.47 in
Weight: 25.2 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 81.2 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 07
Surface temperature: 40°C