


Product data sheet

OTTO II (1-ARMED)
9.888.3142.01
LEIPZIGER LEUCHTEN




Spherical luminaire with mounting height 3.00 - 5.00 m. For medium light requirements. - Sphere mount made of durable polycarbonate - Spherical attachment made of impact-resistant PMMA - All electrical components on a block - special steel frame, painted RAL 9005 -Order pole, dia. 60 mm, separately -Order pole for double-bracket luminaire, dia. 76 mm, separately Voltage: 230V 50Hz Protected to: IP 54 Protection class: II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp			
Nominal lamp power	50 W	LOR	85%
Lamp flux	2000 lm	ULOR	46%
Luminous efficacy	29 lm/W	Total flux	1692 lm
CCT	3400 K	Total power	59 W
CRI	54		



1 x High pressure mercury vapour lamp			
Nominal lamp power	80 W	LOR	85%
Lamp flux	4000 lm	ULOR	46%
Luminous efficacy	38 lm/W	Total flux	3383 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted

Shape and measurements

Height: 15.75 in
Diameter: 15.75 in

Design

Material impression: Matt
Color of housing: Black

Electric

System power: 59-89 W
Ballast: ECG

Protection

IP: 54
Designation labels: CE

Other operating numbers

Ambient temperature range: 14...95°F