## Product data sheet

GEORG V (1-ARMED) 9.870.0124.04

LEIPZIGER LEUCHTEN









With mounting heights between 3.00 and 4.00 m for medium and low light requirements. - Large shade, inside in special white paint for better reflection - Luminaire body made of aluminium/galvanized steel sheet, outside painted in colour, inside finished in special white pain - Impact-resistant polyethylene attachment rotates and locks into place for easy lamp replacement - Steel tubing galvanized and painted -Wired ready for connection - Connection by adapter jack -Available in any RAL or DB colour without surcharge -Order pole for single-bracket luminaire, dia. 60 mm,and pole for multi-bracket luminaire, dia. 76 mm,separately Voltage: 230V 50Hz Protected to: IP 54 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 v High proceure moroup vonour lomp						
1 x High pressure mercury vapour lamp						
Nominal lamp power	50 W	LOR				
Lamp flux	2000 lm	ULOR				
Luminous efficacy	24 lm/W	Total flux				
CCT	3400 K	Total power				
CRI	54					



1 x High pressure mercury vapour lamp					
Nominal lamp power	80 W	LOR	72%		
Lamp flux	4000 lm	ULOR	4%		
Luminous efficacy	32 lm/W	Total flux	2875 lm		
CCT	3400 K	Total power	89 W		
CRI	54				

Mounting mode

Pole top mounted

Shape and measurements

Height: 28.35 in Diameter: 22.83 in Electric

System power: 59-89 W

Protection

IP: 54

72% 4% 1437 lm 59 W