

Product data sheet


MORITZ IV (1-ARMED)
9.117.1032.05
LEIPZIGER LEUCHTEN



IP
55

Mounting height 8.00 m, for medium and high light requirements. -Luminaire made of cast aluminium, varnished - Superior lighting due to computer-optimised reflector system for sodium vapour high pressure discharge with clear glass tube bulb - Cover of single-pane safety glass, hinged - Cable protection hosing made of braided stainless steel - All electrical parts fitted - Available in any required RAL or DB colour without extra price - Curved pole arm with mounting clip, hot-dip galvanised steel, including varnished conical pole for 8.00 m mounting height are part of the delivery - Other heights on request Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x Metal halide lamp

| | | | |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 70 W | LOR | 80% |
| Lamp flux | 7200 lm | Total flux | 5726 lm |
| Luminous efficacy | 64 lm/W | Total power | 89 W |
| CCT | 3000 K | | |
| CRI | 90 | | |

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.26 in
Width: 21.26 in
Height: 6.89 in

Electric

System power: 89 W

Protection

IP: 55