


Product data sheet

TENTEC ACCENT RECESSED LUMINAIRE, SAFETY SCREEN
TL2102504-30-40 + 83817Q10-60_23W
SCHMITZ | WILA



Tentec accent LED 4000 K Recessed Luminaire, Light distribution direct Downlight with lite optic Safety Screen Product: TL2102504-30-40
Operating technology: independent driver required Lite Optic: 83817Q10-60 Lite Optic Safety Screen Tempered safety glass Aluminium reflector (Al99.98), high-polished Half-peak divergence $\alpha = 60^\circ$ Light Technique CRI > 80 High chromaticity stability with 3SDCM (initial) Constant colour temperature 4000 K Lifetime 50.000 h (L70) Luminaire housing stable housing design, made of aluminium die-cast and UV resistant plastics minimised frame thickness of only 2 mm for homogeneous appearance in the ceiling frame colour white, RAL 9016
Operating and assembly technology LED driver to be ordered separately Driver suitable for connection to central battery systems Quick installation due to 2-point screw fixing Suitable for ceiling thicknesses of 12-25 mm (1-12 mm by using optional extension kit, Art.-No. 89081) Reflector with safety suspension Lamp Wattage: 23 W Colour Rendering Index: 80 Colour Temperature: 4000 K Luminaire Luminous Flux: 2120 Lm System Efficiency: 82 Lm/W Half-peak Divergence α : 60° Number Luminaires LZ: 0.06 Connector: screw connector, 2 x 1.5 mm² Reflector Size: Q10 Length: 127 mm Width: 127 mm Cut-out length: 120 mm Cut-out width: 120 mm Installation Depth RD: 110 mm Total Weight: 0.7 kg Degree of Protection IP44, IP44 in closed ceiling systems CE-Sign Total system: Protection class 2 Data record TL2102504-30-40+83817Q10-60_23W

Light output 1



1 x General service incandescent lamp			
Nominal lamp power	26 W	LOR	100%
Lamp flux	2120 lm	Total flux	2120 lm
Luminous efficacy	82 lm/W	Total power	26 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 5.00 in
Width: 5.00 in
Height: 4.33 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 26 W
Appliance Class: II

Protection

IP: 44