

# Product data sheet

SUPERGIÙ\_DIRECT+INDIRECT LIGHT\_WHITE

D59


LUCEPLAN



IP  
20


Un semplice gesto per interagire con la luce. Realizzata in alluminio naturale anodizzato o verniciato consente di avere due illuminazioni diverse: si alza il riflettore e la luce è concentrata verso il basso; si abbassa il riflettore e la luce è omogeneamente diffusa verso l'alto.

## Light output 1




### 1 x Compact fluorescent lamp

|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Nominal lamp power | 23 W    | Socket      | E27    |
| Lamp flux          | 1250 lm | LOR         | 52%    |
| Luminous efficacy  | 4 lm/W  | ULOR        | 19%    |
| CCT                | 3000 K  | Total flux  | 646 lm |
| CRI                | 85      | Total power | 150 W  |



### 1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 140 W   | Socket      | E27     |
| Lamp flux          | 2840 lm | LOR         | 52%     |
| Luminous efficacy  | 10 lm/W | ULOR        | 19%     |
| CCT                | 3000 K  | Total flux  | 1467 lm |
| CRI                | 99      | Total power | 150 W   |



### 1 x Halogen low voltage lamp without reflector

|                    |         |             |         |
|--------------------|---------|-------------|---------|
| Nominal lamp power | 105 W   | Socket      | E27     |
| Lamp flux          | 1980 lm | LOR         | 52%     |
| Luminous efficacy  | 7 lm/W  | ULOR        | 19%     |
| CCT                | 3000 K  | Total flux  | 1023 lm |
| CRI                | 99      | Total power | 150 W   |

## Mounting mode

Pendant

## Electric

System power: 150 W

#### Shape and measurements

Length: 13.86 in

Width: 13.82 in

Height: 14.57 in

#### Adjustability

Height adjustable

#### Protection

IP: 20