

Product data sheet

FLAT POLYMERO XXL
311694.002
RZB




IP
40

IK
07

Series: Flat Polymero XXL Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: sash lock, plastic. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 1040, H 230 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Luminaire flux LED: 9450lm System power: 100W Beam Angle: 117° Number of fittings B10A: 3 Number of fittings B16A: 5 Inrush current: 100A Unified Glare Ratio: 19,2 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	100 W	CRI	80
Total flux	9450 lm	LOR	100%
Luminous efficacy	94 lm/W	ULOR	10%
		Total power	100 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 9.06 in
Diameter: 40.94 in

Adjustability

Fixed

Electric

System power: 100 W

Protection

IP: 40
IK: 07