


# Product data sheet

LIGHT LINEAR VT 6 STREET AND AREA LUMINAIRES  
VT-20024-T1-W40  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K ,4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket and clear toughened glass - Maximum wind load resistance is 120 km/h - Surge protection 10 kV

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	155 W	CRI	80
Total flux	9378 lm	LOR	100%
Luminous efficacy	61 lm/W	Total power	155 W

## Mounting mode

Pole integrated

## Shape and measurements

Length: 3.54 in  
Width: 5.91 in  
Height: 35.24 in  
Weight: 30.4 kg

## Adjustability

Fixed

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 155 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Protection

IP: 65  
IK: 07  
Surface temperature: 40°C